



VERY LOW VOLTAGE BIDIRECTIONAL THYRISTOR OVERVOLTAGE PROTECTORS

TISP4011H1BJ VLV Overvoltage Protector Series


General Information

The protector consists of a symmetrical voltage-triggered bidirectional thyristor. Overvoltages are initially clipped by breakdown clamping until the voltage rises to the breakover level, which causes the device to crowbar into a low-voltage on-state condition. This low-voltage on-state causes the current resulting from the overvoltage to be safely diverted through the device. The device switches off when the diverted current falls below the holding current value.


Agency Recognition

Description	
UL	File Number: E215609

SMB Package (Top View)



Device Symbol



Terminals T and R correspond to the alternative line designators of A and B

Absolute Maximum Ratings, $T_A = 25\text{ }^\circ\text{C}$ (Unless Otherwise Noted)

Rating	Symbol	Value	Unit
Repetitive peak off-state voltage	V_{DRM}	± 5.25	V
Non-repetitive peak on-state pulse current 10/1000 μs 2/10 μs	I_{PPSM}	± 100 ± 500	A
Junction temperature	T_J	-40 to +150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics, $T_A = 25\text{ }^\circ\text{C}$ (Unless Otherwise Noted)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_D Leakage current	$V_D = V_{DRM}$		1	200	μA
$V_{(BO)}$ Breakover voltage	$di/dt = \pm 1\text{ mA}/\mu\text{s}$		9	10.5	V
$I_{(BO)}$ Breakover current	$di/dt = \pm 1\text{ mA}/\mu\text{s}$		75	200	mA
V_T On-state voltage	$I_T = \pm 5\text{ A}$			3	V
I_H Holding current	$I_T = \pm 5\text{ A}$, $di/dt = \pm 1\text{ mA}/\mu\text{s}$	20	60		mA
C_{off} Off-state capacitance	$V_d = 0\text{ V}$, $f = 1\text{ MHz}$, 1 V_{rms}		110		pF

OCTOBER 2016 – REVISED JULY 2019

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice.


Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.



WARNING Cancer and Reproductive Harm
www.P65Warnings.ca.gov

Parameter Measurement Information



PM4AC

Figure 1. Voltage-Current Characteristic for T and R Terminals
All Measurements are Referenced to the R Terminal

How to Order

Device	Package	Carrier	Order as
TISP4011H1BJ	BJ (SMB/DO-214AA J-Bend)	R (Embossed Tape Reeled)	TISP4011H1BJR-S

Carrier Information

For production quantities, the carrier will be embossed tape reel pack. Evaluation quantities may be shipped in bulk pack or embossed tape.

Package	Carrier	Standard Quantity
SMB	Embossed Tape Reel Pack	3000

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

Europe: Tel: +36 88 885 877 • Email: eurocus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

www.bourns.com

OCTOBER 2016 – REVISED JULY 2019

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.