

MODEL TL-4903



International size reference: AA, ER14505

TECHNICAL DATA

(Typical values @+25°C for batteries stored for one year or less)



| | |
|------------------------------------------|------------------|
| ■ Nominal capacity @ 1 mA, to 2 V | 2.4 Ah |
| ■ Rated voltage | 3.6 V |
| ■ Maximum recommended continuous current | 60 mA |
| ■ Maximum 1 sec. pulse capability | 120 mA |
| ■ Weight | 18 g (0.634 oz) |
| ■ Volume | 8 cc |
| ■ Operating temperature range | -55 °C to +85 °C |
| ■ U.L. Component Recognition, MH 12193 | |

TADIRAN
LITHIUM
BATTERIES



AVAILABLE TERMINATIONS

| | |
|----------------------------|---------------|
| SUFFIX- /S STANDARD | 15-4903-21000 |
| SUFFIX- /T SOLDER TABS | 15-4903-31000 |
| SUFFIX- /P AXIAL PINS | 15-4903-41000 |
| SUFFIX- /PT2 RADIAL PINS | 15-4903-36000 |
| SUFFIX- /TP POLARIZED TABS | 15-4903-52000 |
| SUFFIX- /PT POLARIZED TABS | 15-4903-53000 |



XOL - Extended Operating Life

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. D 01/07 ECN1501458