



Part Number:	TP124003-2	
	DRAWN	9/22/2016
	CJ	
Description:	CHECKED	9/22/2016
	P.D.	
	APPROVED	9/22/2016
J.S.		
This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com		


Side View (1)




Top View




Side View (2)




Bottom View



Layout Pattern



Front View



Items	Specifications	Conditions
Sound Pressure Level	75	dB (@ 10cm)
Resonant Frequency	4,000	Hz
Rated Voltage	3	V
Voltage Range	1 ~ 25	V
Capacitance	16,000	pF
Max. Rated Current	5	mA
Storage Temperature	-40 ~ +85	°C
Operating Temperature	-40 ~ +85	°C
Connection Method	Surface Mount Pads	
Mount Type	Surface Mount	
Housing Material	LCP	
Weight	0.3	g

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
	Released from Engineering	10/21/2013	J.S.
1	Updated Operating and Storage Temperature	8/7/2014	C.E.
2	1.) Sound Emission hole 0.9 mm change to 1.3 mm 2.) Modified Date Code Marking	11/17/2015	C.E.
3	Updated to new template	9/22/2016	C.E.
4	Sound Emission Hole change 1.3mm to 1.1mm	2/24/2017	C.E.

NOTES			
1) All dimensions are in mm unless otherwise noted			
2) All tolerances are ± 0.5 mm unless otherwise noted			
3) All parts meet RoHS			
4) Subject to change or redrawn without notice			