

Surface Mount


RF Transformer

TRS2-32-75+

75Ω 1 to 300 MHz

The Big Deal

- Low insertion loss, 0.5 dB typ.
- Good return loss, 25 dB typ.
- Low unbalance, 0.2 dB, 2°
- Power handling up to 0.25W



CASE STYLE: AT577-2

Product Overview

Mini-Circuits TRS2-32-75+ is a 75Ω surface mount balun transformer with a 1:2 secondary/primary impedance ratio covering the 1 to 300 MHz band. This model handles RF input power up to 0.25W and provides low insertion loss, good return loss, low amplitude unbalance, and low phase unbalance. Measuring only 0.2 x 0.2 x 0.15", the unit features core and wire, all-welded construction mounted on a six-lead printed wiring laminate base with wraparound terminations for excellent solderability. The unit also includes Mini-Circuits' Top Hat™ feature for faster more accurate pick-and-place assembly.

Key Features

Feature	Advantages
Wideband, 1 to 300 MHz, Usable to 500 MHz	TRS2-32-75+ supports a variety of applications including CATV and DOCSIS® 3.1 upstream paths.
Low insertion loss, 0.5 dB	Enables excellent signal power transmission from input to output.
Good return loss, 25 dB typ.	Excellent matching for 75Ω systems with minimal signal reflection.
Low unbalance • 0.2 dB amplitude unbalance • 2° phase unbalance	Low unbalance can improve a system's electromagnetic compatibility by rejecting unwanted common-mode noise.
Small footprint, 0.2 x 0.2"	Accommodates tight space requirements for dense PCB layouts.
Top Hat® feature	Improves speed and accuracy of pick and place assembly and provides clear device marking for visual inspection

Ceramic Balun RF Transformer

TRS2-32-75+


75Ω 1 to 300 MHz

Features

- wideband, 1 to 300 MHz
- useable up to 500 MHz
- good return loss
- flat insertion loss

Applications

- impedance matching
- balanced to unbalanced transformer
- push-pull amplifiers
- CATV



Generic photo used for illustration purposes only

CASE STYLE:AT577-2

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Impedance Ratio (secondary/primary)			0.5		
Frequency Range		1	—	300	MHz
Insertion Loss	1-300	—	0.6	1.1	dB
Amplitude Unbalance	1-300	—	0.2	0.5	dB
Phase Unbalance	1-300	—	2	6	Degree

Note: External capacitors $C_p = 2.0\text{pF}$ and $C_{s1} = C_{s2} = 18\text{pF}$ must be added to achieve specify performance. Suggested size 0402.

Maximum Ratings


Parameter	Ratings
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	0.25W
DC Current	30mA

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

Function	Pin Number
PRIMARY DOT	3
PRIMARY	1
SECONDARY DOT	6
SECONDARY	4
AC GND (DC BIAS)	2
ISOLATED	5

Product Marking



Configuration J1

