

75Ω 30 to 3000 MHz

The Big Deal

- Wideband, 30 to 3000 MHz
- Low insertion loss, 1.5 dB typ.
- Good amplitude unbalance, ± 0.4 dB typ.
- Low phase unbalance, 4° typ.
- Excellent common mode rejection, 26 dB typ.



CASE STYLE: GU2939

Product Overview

Mini-Circuits' TTC1-33W-75+ is a tiny surface-mount transmission line core and wire transformer covering a very wide frequency range from 30 to 3000 MHz. The transformer provides low insertion loss. It achieves low phase and amplitude unbalance and excellent common mode rejection performance. Featuring core and wire construction on 5 terminal carrier, the unit measures 0.10 x 0.06 x 0.07", accommodating dense circuit board layouts.

Key Features

Feature	Advantages
Wideband, 30 to 3000 MHz	Very wide frequency range covers bandwidth requirements for many broadband applications.
Low insertion loss, 1.5 dB typ.	TTC1-33W-75+ provides excellent signal transmission from input to output with consistent performance across its entire frequency range.
Excellent common mode rejection, 26 dB typ.	Provides good IP2, IP3.
Small footprint (0.10 x 0.06 x 0.07")	Accommodates tight space requirements for dense PCB layouts.

Surface Mount RF Transformer

75Ω 30 to 3000 MHz

TTC1-33W-75+



Generic photo used for illustration purposes only

CASE STYLE: GU2939

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000, 2000

Features

- wide bandwidth 30 to 3000 MHz
- balanced transmission line
- excellent CMRR
- aqueous washable

Applications

- CATV
- wideband push-pull amplifiers
- cellular

Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Impedance Ratio			1		
Frequency Range		30		3000	MHz
Average Insertion Loss (above nominal loss 0.3 dB)	50-870	—	0.6	1.0	dB
	45-1760	—	1.2	1.5	
	30-3000	—	2.0	3.0	
Phase Unbalance (±)	45-1760	—	4	9	Degree
	30-3000	—	9	—	
Amplitude Unbalance	45-1760	—	0.4	1.5	dB
	30-3000	—	0.8	1.9	
Return Loss	45-1760	—	16	—	dB
Common Mode Rejection	45-1760	20	26	—	dB
	30-3000	18	22	—	

Maximum Ratings

Parameter	Ratings
Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	0.5W

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

Function	Pin Number
PRIMARY DOT	1
PRIMARY	4
SECONDARY DOT	2
SECONDARY	3
NOT USED	5

Config. G

