

T1/CEPT/ISDN-PRI TRANSFORMERS

Dual Surface Mount, 1500Vrms, Extended and Standard Temperature Range



- Dual SMT package contains both transmit and receive transformers
- Models matched to leading transceiver ICs
- Isolation voltage: 1500Vrms
- UL recognized
- RoHS compliant versions available

Electrical Specifications @ 25°C

| Part Number | Turns Ratio ^B (Pri:Sec ± 2%) | OCL @ 25°C (mH MIN) | L _L (μH MAX) | C _{w/w} (pF MAX) | DCR Pri (Ω MAX) | DCR Sec (Ω MAX) | Package/ Schematic | Primary Pins |
|---|--|------------------------|----------------------------|------------------------------|--------------------|--------------------|-----------------------|-----------------|
| EXTENDED TEMPERATURE RANGE MODELS¹ – OPERATING TEMPERATURE -40°C TO +85°C | | | | | | | | |
| PE-68841 | 1CT:2CT & 1CT:2CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.00 & 1.00 | 1.70 & 1.70 | AN/2 | 12-10, 4-6 |
| PE-68822 | 1CT:2CT & 1:1.36CT | 1.60 & 1.60 | 1.00 & 0.80 | 60 & 55 | 1.70 & 1.70 | 2.00 & 1.70 | AN/1 | 12-10, 4-6 |
| PE-68825 | 1:1.15CT & 1CT:2CT | 1.60 & 1.60 | 0.80 & 0.80 | 60 & 50 | 1.00 & 1.00 | 1.20 & 2.00 | AN/4 | 12-10, 4-6 |
| PE-68826 ^E | 1:1/1.26 & 1:2CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 60 | 1.00 & 1.00 | 1.10 & 1.70 | AN/5 | 12-10, 4-6 |
| PE-68827 | 1:1CT & 2:1 | 1.60 & 1.60 | 1.30 & 1.30 | 55 & 40 | 1.10 & 1.10 | 1.10 & 0.70 | AN/6 | 1-3, 4-6 |
| PE-68828 | 1CT:1CT & 1CT:1CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.00 & 1.00 | 1.00 & 1.00 | AN/2 | 1-3, 4-6 |
| PE-68874 | 1CT:1.15CT & 1CT:1.15CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.20 & 1.20 | 1.40 & 1.40 | AN/2 | 1-3, 4-6 |
| PE-68877 | 1CT:1CT & 1CT:2CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.00 & 1.00 | 1.00 & 1.80 | AN/2 | 1-3, 4-6 |
| PE-68882 | 1CT:1.15CT & 1CT:1CT | 1.60 & 1.60 | 0.80 & 0.80 | 60 & 60 | 1.20 & 1.20 | 1.40 & 1.20 | AN/2 | 12-10, 4-6 |
| PE-68884 | 1CT:1.36CT & 1CT:1.36CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.20 & 1.20 | 1.40 & 1.40 | AN/2 | 1-3, 4-6 |
| PE-68887 | 1CT:1.41CT & 1CT:1.41CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.40 & 1.40 | 1.20 & 1.20 | AN/2 | 12-10, 9-7 |
| PE-68881 | 1CT:2.3CT & 1CT:2CT | 1.20 & 1.20 | 0.80 & 0.80 | 60 & 50 | 1.20 & 1.20 | 2.10 & 2.10 | AN/2 | 10-12, 4-6 |
| TX1277 | 1CT:1CT & 1CT:2CT | 1.20 & 1.20 | 0.80 & 0.80 | 50 & 50 | 1.00 & 1.00 | 1.00 & 1.80 | AN/2 | 1-3, 4-6 |
| STANDARD TEMPERATURE RANGE MODELS – OPERATING TEMPERATURE 0°C TO +70°C | | | | | | | | |
| T1131 ¹ | 1CT:1 & 1:1.36CT | 0.70 & 0.70 | 0.70 & 0.70 | 20 & 20 | 0.25 & 0.50 | 0.80 & 0.40 | AN/7 | 1-3, 9-7 |
| PE-68861 | 1CT:2CT & 1CT:2CT | 1.20 & 1.20 | 0.60 & 0.60 | 35 & 35 | 0.70 & 0.70 | 1.20 & 1.20 | AN/2 | 12-10, 4-6 |
| PE-68862 | 1CT:2CT & 1:1.36CT | 1.20 & 1.20 | 0.60 & 0.80 | 35 & 37 | 0.70 & 0.70 | 1.20 & 0.90 | AN/1 | 12-10, 4-6 |
| PE-68863 | 1:2CT & 1:1.14CT | 1.20 & 1.20 | 0.55 & 0.80 | 40 & 35 | 0.70 & 0.70 | 1.20 & 0.90 | AN/5 | 12-10, 4-6 |
| PE-68864 ^A | 1CT:2CT & 1:1 | 1.20 & 1.20 | 0.30-0.55 & 0.80 | 30 & 30 | 0.70 & 0.70 | 1.20 & 0.70 | AN/3 | 1-3, 5-6 |
| PE-68865 | 1:1.15CT & 1CT:2CT | 1.50 & 1.20 | 0.80 & 0.60 | 35 & 35 | 0.70 & 0.70 | 0.90 & 1.20 | AN/4 | 12-10, 4-6 |
| PE-68866 ^E | 1:1/1.26 & 1:2CT | 1.50 & 1.20 | 0.40 & 0.50 | 40 & 40 | 0.70 & 0.70 | 0.90 & 1.20 | AN/5 | 12-10, 4-6 |
| PE-68869 | 1CT:2CT & 1:1.08CT | 1.20 & 1.20 | 0.60 & 0.60 | 40 & 30 | 0.70 & 0.70 | 1.10 & 0.90 | AN/1 | 12-10, 4-6 |
| PE-68836 ^E | 1:1/1.26 & 1:1/1.26 | 1.50 & 1.50 | 0.40 & 0.40 | 45 & 45 | 0.80 & 0.80 | 1.00 & 1.00 | AN/7 | 12-10, 9-7 |

Note: RoHS-6 compliant parts can be ordered by adding an "NL" suffix to the part number (i.e. PE-68841 becomes PE-68841NL). (See Pages 6 and 7 for Table Notes)

Mechanical

Schematics

AN

Dimensions: .675 MAX (17,15), .600 MAX (15,24), .085 (2,16), .100 (2,54), .456 MAX (11,58), .340 MAX (8,64), .040/0,10 MAX, .120 (3,05), .050 TYP (1,27), .640 (16,26), .400 (10,16), .500 (12,70), .100 TYP (2,54), .010 / .020 (0,25 / 0,51), .040 / .050 (1,02 / 1,27), 0°-8°

SUGGESTED PAD LAYOUT

1 2 3 4 5 6 7

Weight 4.0 grams
Tape & Reel250/reel
Tube30/tube

Dimensions: Inches
mm
Unless otherwise specified,
all tolerances are ± .010
0,25

T1/CEPT/ISDN-PRI TRANSFORMERS

Dual Surface Mount, 1500Vrms, Small Package



- Dual SMT package contains both transmit and receive transformers
- Models matched to leading transceiver ICs
- UL recognized (some parts pending approval)
- RoHS compliant versions available upon request

Electrical Specifications @ 25°C

| Part # (STD temp.) | Part # (EXT temp.) | Turns Ratio ^B (Pri:Sec ±5%) | OCL (mH MIN) | C _{w/w} (pF MAX) | L _L (μH MAX) | DCR Pri (Ω MAX) | Package/ Schematic | Primary Pins |
|-----------------------|-----------------------|---|-----------------|------------------------------|----------------------------|--------------------|-----------------------|-----------------|
| PE-65861 | T1090 | 1CT:2CT & 1CT:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 16-14, 6-8 |
| PE-65862 | T1091 | 1CT:2CT & 1:1.36CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/2 | 16-14, 6-8 |
| PE-65865 | T1076 | 1:1.15CT & 1CT:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/3 | 16-14, 6-8 |
| PE-65866 ^E | T1092 ^E | 1:1/1.26 & 1CT:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/3 | 16-14, 6-8 |
| PE-65870 | T1093 | 1CT:1.15CT & 1CT:1.15CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| T1022 | T1077 | 1CT:1CT & 1CT:1.5CT | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 0.70 & 0.70 | BH/1 | 16-14, 6-8 |
| PE-68678 | T1094 | 1CT:1CT & 1CT:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 16-14, 6-8 |
| PE-68786 | T1095 | 1CT:1.41CT & 1CT:1.41CT | 1.00 & 1.00 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 16-14, 11-9 |
| T1023 | T1096 | 1CT:1.41CT & 1CT:1.41CT | 1.00 & 1.00 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 1-3, 11-9 |
| — | T1144 | 1CT:1CT & 1CT:2.4CT | 1.00 & 1.00 | 30 & 30 | .80 & .80 | 0.85 & 0.85 | BH/1 | 9-11, 1-3 |
| — | T1097 | 1CT:1CT & 1CT:1.67CT | 1.00 & 1.00 | 25 & 25 | .80 & .80 | 0.80 & 0.80 | BH/1 | 6-8, 14-16 |
| T1136 | — | 1CT:1CT & 1CT:1.36CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 6-8, 1-3 |
| T1121 | — | 1CT:1.5CT & 1CT:1.5CT | 1.50 & 1.50 | 40 & 40 | .80 & .80 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| T1122 | — | 1CT:2CT & 1CT:2.3CT | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 0.90 & 0.90 | BH/1 | 6-8, 14-16 |
| T1021 ^I | — | 2CT:1/1.26 & 2CT:1/1.26 | 1.50 & 1.50 | 40 & 40 | .50 & .50 | 0.70 & 0.70 | BH/1 | 1-3, 11-9 |
| T1075 ^I | — | 2CS:1.57/2 & 2CS:1.57/2 | 1.50 & 1.50 | 40 & 40 | .50 & .50 | 0.70 & 0.70 | BH/4 | 1-2, 5-6 |
| T1190 | — | 1CT:1CT & 1CT:1.36CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 16-14, 6-8 |
| T1137 | TX1287 | 1CT:2.42CT & 1CT:2.42CT | 1.20 & 1.20 | 25 & 25 | .60 & .60 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| — | T1146 | 1:2/2.4 & 1:0.79/1 | 1.00 & 1.00 | 35 & 35 | 1.00 & 1.00 | 0.80 & 0.80 | BH/5 | 1-3, 6-8 |
| T1286 | — | 1CT:2.4CT & 1CT:2.4CT | 1.20 & 1.20 | 15 & 15 | .30 & .30 | 0.30 & 0.30 | BH/1 | 1-3, 6-8 |
| — | TX1317 | 1:2CT & 1:2CS | 1.20 & 1.20 | 35 & 35 | .50 & 1.00 | 1.00 & 1.00 | BH/6 | 1-3, 11-9 |
| — | TX1189 | 1:1.36CT & 1:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 1.00 & 1.00 | BH/7 | 16-14, 6-8 |
| — | TX1188 | 1CT:2CT & 1CT:2CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| — | TX1187 | 1CT:2CT & 1:1 | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/8 | 1-3, 6-8 |
| — | TX1088 | 1CT:2CT & 1CT:2.42CT | 1.20 & 1.20 | 35 & 35 | .80 & .80 | 1.00 & 1.00 | BH/1 | 1-3, 6-8 |
| — | TX1089 | 1CT:1CT & 1CT:1CT | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| — | TX1098 | 1CT:1.26CT & 1CT:1.26CT | 1.20 & 1.20 | 30 & 30 | .60 & .60 | 0.70 & 0.70 | BH/1 | 1-3, 6-8 |
| — | TX1099 | 1CT:1:0.8 & 1CT:1:0.8 | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 1.00 & 1.00 | BH/4 | 16-14, 11-9 |
| — | TX1186 | 1CT:1.58:2 & 1:1.65:2 | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 1.00 & 1.00 | BH/9 | 2-4, 6-7 |
| — | TX1467 | 1CT:1:1 & 1CT:1:1 | 1.20 & 1.20 | 30 & 30 | .80 & .80 | 1.00 & 1.00 | BH/4 | 16-14, 11-9 |

NOTE: Standard (STD) operating temperature range is 0°C to 70°C. Extended (EXT) operating temperature range is -40°C to +85°C. RoHS-6 compliant parts can be ordered by adding an "NL" suffix to the part number (i.e. PE-65861 becomes PE-65861NL). (See Pages 6 and 7 for Table Notes)

Mechanical


Schematics

Weight 1.0 grams
Tape & Reel 600/reel
Tube 40/tube

Dimensions: Inches / mm
 Unless otherwise specified, all tolerances are ± .010 / 0.25

T1/CEPT/ISDN-PRI TRANSFORMERS

Single Reinforced Insulation, 3KVrms



- Certified for reinforced insulation per UL
- For T1/CEPT line interfaces
- Matched to leading transceiver ICs
- Designed to meet ITU-T G.703
- RoHS compliant versions available upon request

Electrical Specifications @ 25°C — Operating Temperature 0°C to 70°C (Unless Otherwise Noted)

| Part Number | Turns Ratio ^B (±5%) | OCL ^B (mH MIN) | C _{WWW} (pF MAX) | L _L (μH MAX) | DCR Pri (Ω MAX) | DCR Sec (Ω MAX) | Safety Agency Recognition ¹⁰ | Package/Schematic | Primary Pins |
|-----------------------|-----------------------------------|------------------------------|------------------------------|----------------------------|--------------------|--------------------|---|-------------------|--------------|
| PE-65830 | 1.27CS:1 | .800 | 15 | 0.70 | 0.50 | 0.35 | C,T,U,B | IS/3 | 1-5 |
| PE-65831 | 1CS:1 | .800 | 15 | 0.70 | 0.50 | 0.45 | C,T,U,B | IS/3 | 1-5 |
| PE-65832 | 1:1.36CT | 1.20 | 35 | 0.60 | 0.70 | 0.90 | C,T,U,B | IS/4 | 10-6 |
| PE-65833 ^A | 1CT:2CT | 1.20 | 20 | 0.30-0.55 | 0.50 | 0.90 | C,T,U,B | IS/1 | 1-5 |
| PE-65834 | 1:1 | 1.20 | 20 | 0.50 | 0.50 | 0.50 | C,T,U,B | IS/2 | 1-5 |
| PE-65835 | 1CT:2CT | 1.20 | 15 | 0.80 | 0.70 | 1.10 | C,T,U,B | IS/1 | 1-5 |
| PE-65836 | 1CT:3CT:1 | .600 | 30 | 0.80 | 0.70 | 1.70 | C,T,U,B | IS/5 | 1-3 |
| PE-65837 ^E | 1:1.08/1.36 | 1.50 | 20 | 0.60 | 0.70 | 0.90 | C,T,U,B | IS/4 | 10-6 |
| PE-65838 | 1:1.14CT | 1.50 | 30 | 1.00 | 0.70 | 0.90 | C,T,U,B | IS/4 | 10-6 |
| PE-65839 ^E | 1:1/1.26 | 1.50 | 35 | 0.60 | 0.70 | 1.10 | C,T,U,B | IS/4 | 10-6 |
| PE-68646 ^E | 1:1.58/2 | 1.50 | 20 | 0.70 | 0.70 | 1.20 | C,T,U,B | IS/4 | 10-6 |
| PE-68788 | 1CT:1.41CT | 1.20 | 20 | 0.80 | 0.60 | 0.80 | T,U,B | IS/1 | 10-6 |




NOTE: RoHS-6 compliant parts can be ordered by adding an "NL" suffix to the part number (i.e. PE-65830 becomes PE-65830NL).

(See Pages 6 and 7 for Table Notes)

Mechanical

Schematics


IS



Notes:
Leads are 22 AWG solderable.
Unused pins not provided.


Weight 4 grams
Tube35/tube

Dimensions: Inches
mm
Unless otherwise specified,
all tolerances are ± .010
0,25



T1/CEPT/ISDN-PRI TRANSFORMERS

Single Through Hole, 1500Vrms



- Extended and standard temperature range
- Dual and single through hole models available
- Models matched to leading transceiver ICs
- UL recognized
- Isolation Voltage: 1500Vrms MIN
- RoHS compliant versions available upon request

Electrical Specifications @ 25°C



| Part Number | Turns Ratio ^B (Pri:Sec ±5%) | OCL @ 25°C (mH MIN) | C _{w/w} (pF MAX) | L _L (μH MAX) | DCR Pri (Ω MAX) | DCR Sec (Ω MAX) | Package/ Schematic | Primary Pins |
|--|---|------------------------|------------------------------|----------------------------|--------------------|--------------------|-----------------------|-----------------|
| STANDARD TEMPERATURE RANGE SINGLE TRANSFORMERS – OPERATING TEMPERATURE 0°C TO +70°C | | | | | | | | |
| PE-64931 | 1:1:1 (1:2CS) | 1.20 | 25 | 0.50 | 0.70 | 0.70 & 0.70 | HC/2 | 1-2 |
| PE-64933 | 1CT:3CT | 1.20 | 30 | 0.50 | 0.70 | 1.60 | HC/4 | 1-5 |
| PE-64934 | 1:1 | 1.20 | 25 | 0.50 | 0.70 | 0.70 | HC/1 | 1-2 |
| PE-64936 | 1CT:1 | 1.20 | 25 | 0.80 | 0.70 | 0.70 | HC/3 | 1-5 |
| PE-64937 | 1:1.36 | 1.20 | 35 | 0.80 | 0.70 | 0.80 | HC/1 | 5-6 |
| PE-64940 | 1.26CS:1 (1:1:1.58) | 0.30 | 30 | 0.60 | 0.80 | 0.60 | HC/2 | 1-4 |
| PE-64941 ^D | 1CS:1 | 0.80 | 30 | 0.60 | 0.80 | 0.60 | HC/2 | 1-4 |
| PE-64942 | 1CS:1.31 | 0.80 | 30 | 0.40 | 0.80 | 0.60 | HC/2 | 1-4 |
| PE-64943 ^A | 1CT:2CT | 1.20 | 30 | 0.30-0.55 | 0.70 | 1.20 | HC/4 | 1-5 |
| PE-65351 | 1:2CT | 1.20 | 40 | 0.50 | 0.70 | 1.30 | HC/3 | 2-6 |
| PE-65363 | 1:4CT | 0.50 | 40 | 1.00 | 0.50 | 1.50 | HC/5 | 1-5 |
| PE-65379 | 1:1.14CT | 1.20 | 35 | 0.80 | 0.70 | 0.80 | HC/5 | 1-5 |
| PE-65388 | 1:1.15CT | 1.50 | 35 | 0.60 | 0.70 | 0.90 | HC/3 | 2-6 |
| PE-65389 ^E | 1:1/1.26 | 1.50 | 40 | 0.40 | 0.70 | 0.90 | HC/3 | 2-6 |
| PE-65415 | 1CT:2CT | 1.20 | 30 | 0.50 | 0.70 | 1.20 | HC/4 | 1-5 |
| PE-65558 | 1:2.3CT | 1.20 | 35 | 0.80 | 0.70 | 1.40 | HC/5 | 1-5 |
| PE-65586 | 1:1.36CT | 1.20 | 35 | 0.80 | 0.70 | 0.90 | HC/5 | 1-5 |
| PE-65755 | 1CT:1CT | 1.20 | 25 | 0.80 | 0.80 | 0.80 | HC/4 | 1-5 |
| PE-68644 | 1CT:1 | 0.70 | 20 | 0.70 | 0.20 | 0.80 | HC/3 | 1-5 |
| PE-68645 | 1:1.36CT | 0.70 | 20 | 0.70 | 0.50 | 0.40 | HC/5 | 1-5 |
| T1054 | 1:1.5CT | 1.20 | 30 | 0.60 | 0.70 | 1.00 | HC/3 | 2-6 |
| T1249 | 1:1.26CT | 1.20 | 60 | 0.80 | 0.90 | 1.00 | HC/4 | 2-6 |
| EXTENDED TEMPERATURE RANGE SINGLE TRANSFORMERS 1 – OPERATING TEMPERATURE -40°C TO +85°C | | | | | | | | |
| PE-65340 | 1:1.36 | 1.20 | 35 | 0.80 | 0.90 | 1.20 | HC/1 | 5-6 |
| PE-65770 | 1:1.15CT | 1.50 | 40 | 0.80 | 0.90 | 1.00 | HC/3 | 2-6 |
| PE-65771 | 1CT:2CT | 1.20 | 50 | 0.60 | 1.00 | 2.00 | HC/4 | 2-6 |
| PE-65778 | 1CT:1CT | 1.20 | 40 | 1.00 | 1.00 | 1.00 | HC/4 | 1-5 |
| PE-68600 | 1CT:3CT | 1.20 | 60 | 0.80 | 0.90 | 2.70 | HC/4 | 1-5 |
| PE-68664 ^E | 1:1/1.26 | 1.50 | 50 | 0.80 | 0.90 | 1.10 | HC/3 | 2-6 |
| TX1252 | 1CT:1 | 1.20 | 40 | 1.00 | 1.00 | 1.00 | HC/3 | 1-5 |

NOTE: RoHS-6 compliant parts can be ordered by adding an "NL" suffix to the part number (i.e. PE-64931 becomes PE-64931NL).

(See Pages 6 and 7 for Table Notes)

Mechanical

Schematics



T1/CEPT/ISDN-PRI TRANSFORMERS

Dual Through Hole, 1500Vrms



Electrical Specifications @ 25°C

| Part Number | Turns Ratio ^B (Pri:Sec ±5%) | OCL @ 25°C (mH MIN) | C _{w/w} (pF MAX) | L _L (μH MAX) | DCR Pri (Ω MAX) | DCR Sec (Ω MAX) | Package/ Schematic | Primary Pins |
|---|---|------------------------|------------------------------|----------------------------|--------------------|--------------------|-----------------------|-----------------|
| STANDARD TEMPERATURE RANGE DUAL TRANSFORMERS – OPERATING TEMPERATURE 0°C TO +70°C | | | | | | | | |
| PE-64951 | 1:2CT & 1:2CT | 1.20 & 1.20 | 35 & 35 | 0.50 & 0.50 | 0.70 & 0.70 | 1.20 & 1.20 | HD/1 | 14-12, 5-7 |
| PE-64952 | 1:2CT & 1:1.36 | 1.20 & 1.20 | 35 & 35 | 0.50 & 0.80 | 0.80 & 0.80 | 1.20 & 1.00 | HD/2 | 14-12, 5-7 |
| PE-64953 | 1:2CT & 1:2CT | 2.00 & 2.00 | 50 & 50 | 0.60 & 0.60 | 1.00 & 1.00 | 2.00 & 2.00 | HD/3 | 14-12, 10-8 |
| PE-64954 ^A | 1CT:2CT & 1:1 | 1.20 & 1.20 | 30 & 30 | 0.30-0.55 & 0.50 | 0.70 & 0.70 | 1.20 & 0.70 | HD/4 | 1-3, 5-7 |
| PE-64955 | 1:1.26CT & 1.58:1 | 0.80 & 0.80 | 30 & 30 | 0.50 & 0.50 | 0.60 & 0.60 | 0.70 & 0.30 | HD/5 | 1-3, 5-7 |
| PE-64956 | 1:1CT & 2:1 | 0.80 & 0.80 | 30 & 30 | 0.60 & 0.60 | 0.50 & 0.50 | 0.50 & 0.20 | HD/5 | 1-3, 5-7 |
| PE-64957 | 1CT:1.31 & 2.62:1 | 1.20 & 1.20 | 30 & 30 | 0.80 & 0.80 | 0.60 & 0.60 | 0.50 & 0.30 | HD/5 | 1-3, 5-7 |
| PE-65565 | 1:1.15CT & 1:2CT | 1.50 & 1.20 | 35 & 40 | 0.60 & 0.50 | 0.70 & 0.70 | 1.10 & 1.30 | TD/1 | 14-12, 5-7 |
| PE-65566 ^E | 1:1/1.26 & 1:2CT | 1.50 & 1.20 | 40 & 40 | 0.50 & 0.40 | 0.70 & 0.70 | 0.90 & 1.30 | TD/1 | 14-12, 5-7 |
| EXTENDED TEMPERATURE RANGE DUAL TRANSFORMERS ¹ – OPERATING TEMPERATURE -40°C TO +85°C | | | | | | | | |
| PE-65567 | 1:1.15CT & 1:2CT | 1.50 & 1.20 | 40 & 60 | 0.80 & 0.80 | 0.90 & 0.90 | 1.00 & 1.70 | TD/1 | 14-12, 5-7 |
| PE-65568 ^E | 1:1/1.26 & 1:2CT | 1.50 & 1.20 | 50 & 60 | 0.80 & 0.80 | 0.90 & 0.90 | 1.00 & 1.70 | TD/1 | 14-12, 5-7 |
| PE-65774 | 1CT:2CT & 1:1.36CT | 1.20 & 1.20 | 50 & 50 | 0.96 & 0.80 | 1.00 & 1.00 | 1.70 & 1.20 | TD/7 | 14-12, 5-7 |
| PE-68618 ^G | 1CT:1CT & 3CT:1CT:25 | 1.20 & 32.0 | 40 & 65 | 0.80 & 0.80 | 1.00 & 3.00 | 1.00 & 1.20 | BD/6 | 1-3, 11-9 |
| PE-64950 ^G | 1CT:1CT & 1CT:3CT:1 | 1.20 & 0.60 | 50 & 50 | 0.80 & 0.80 | 1.00 & 0.80 | 1.00 & 2.00 | BD/6 | 1-3, 4-6 |

(See Pages 6 and 7 for Table Notes)

Mechanicals

TD
DUAL

Weight 2.6 grams
Tube25/tube

HD
DUAL

Weight 2.3 grams
Tube25/tube

BD
DUAL

Weight 3.1 grams
Tube25/tube

Note: Leads are 24 AWG solderable.

Dimensions: Inches
mm

Unless otherwise specified all tolerances are ±.010
0,25

Schematics

1: PE-64951, PE-64952, PE-64953, PE-64954, PE-64955, PE-64956, PE-64957

2: PE-64954, PE-64955, PE-64956, PE-64957

3: PE-64951, PE-64952, PE-64953, PE-64954, PE-64955, PE-64956, PE-64957

4: PE-64951, PE-64952, PE-64953, PE-64954, PE-64955, PE-64956, PE-64957

5: PE-64951, PE-64952, PE-64953, PE-64954, PE-64955, PE-64956, PE-64957

6: PE-68618, PE-64950

7: PE-65774

USA 858 674 8100 • Germany 49 7032 7806 0 • Singapore 65 6287 8998 • Shanghai 86 21 32181071 • China 86 755 33966678 • Taiwan 886 3 4643715

www.pulseeng.com

5


T608.S (4/08)

T1/CEPT/ISDN-PRI TRANSFORMERS


Application Notes



- Extended Temperature Range Models** — For extended temperature range transformers (-40°C to +85°C operating temperature range), OCL (Open Circuit Inductance for the primary winding) is specified at both -40°C and +25°C. At -40°C, OCL is 600 μH minimum for all low temperature models with the exception of PE-68827 which is 800 μH minimum and PE-65836 which is 300 μH minimum. All other parameters are specified at +25°C only. Standard temperature range is 0°C to +70°C.
- ET Product** — All coils have an ET product of 10 V-μsec minimum.
- Flammability** — Materials used in the products are recognized as UL94-VO approved. Products meet the requirements of IEC 695-2-2 (Needle Flame Test).
- Balance Characteristics** — The transformers meet the requirements for longitudinal balance of FCC part 68.
- Common Mode Rejection Ratio** — the CMRR for all transformers is better than 50 dB at 1 MHz. A typical test circuit is shown below.



- Crosstalk Attenuation** — In the dual packages, which contain transmit and receive transformers side by side, sufficient crosstalk attenuation is achieved by the inherent characteristics of the toroid cores as well as by their proper positioning. The crosstalk attenuation is typically 50 dB or better from 100kHz to 10MHz. This result was established with the test circuit shown below.



- Return Loss** — ITU-T G.703 and European national regulatory documents specify minimum return loss levels. The transformers will allow these limits to be complied within the situations where they are applicable.

| Frequency | 50-100kHz | 100kHz-2 MHz | 2-3MHz |
|-------------|-----------|--------------|--------|
| Return Loss | | | |
| XMIT | 9 dB | 15dB | 11dB |
| REC | 12 dB | 18dB | 14dB |

- Surge Voltage Capability** — All transformers and chokes meet surge voltage tests according to the most stringent regulatory documents when system designs include the proper voltage and current suppression devices:

Metallic Voltage: 800V peak, 10/560μsec
 Longitudinal Voltage: 2,400V peak, 10/700μsec

- Isolation Voltage** — 100% of transformers are tested during production to the specified isolation voltage level.

- Safety Agency Recognition** — Parts listed as "Recognized" or "Certified" meet Underwriter Laboratories, UL 1459 and UL 1950 per file E133523 (S).


Transformers with Reinforced Insulation according to IEC950 series PE-68630—PE-68788 (pg. 3) are certified by the following organizations:

| Code | Certificate Information |
|------|---|
| T | TÜV, EN 60 950/EN 41003, Cert. R9371358, reinforced insulation. |
| U | UL 1459/UL1950, File E133523 (S), reinforced insulation. |

- General Information** — The transformers are specifically designed for use in 1.544 Mbps (T1), 2.048 Mbps (CEPT) and ISDN Primary rate (PRI) interface applications. They are matched to the majority of the line interface transceiver ICs currently available. Use of the proper transformer allows the interface circuit to comply with ITU-T G.703 and other standards regarding pulse waveform, return loss, and balance.

- Common Mode Chokes** — The "high-frequency" 4-lines common mode chokes shown in this data sheet provide an effective means of compliance with national and international regulations on EMI. They are designed to be used in conjunction with Pulse's T1/CEPT transformers as shown in the typical application below. Crosstalk is typically -70dB at 1MHz and -55dB at 10MHz.

Typical Application



NOTES FROM TABLES (pages 1 through 6):

- Toleranced leakage inductance: .30μH min to .55μH MAX.
- OCL (primary inductance) and LL (leakage inductance) are measured at the primary winding. Turns ratio is specified primary: secondary. (CT = Center Tap; CS = Split Center Tap).
- To make a 1CT:1 ratio from a 1CT:2CT ratio, use only one half of the secondary (2CT) winding.
- For Reinforced 3kVrms Dual SMT Transformers, refer to data sheet T617. For Quad SMT Transformers refer to data sheet T615. For Octal SMT Transformers refer to data sheet T622.
- Dual Ratio Transformers — These transformers have tapped secondary windings to provide two turns ratios (T/R). Use the entire primary winding and connect the secondary pins listed below to obtain the desired turns ratio:

| Part Number | Turns Ratio 1 | Secondary Pins | Turns Ratio 2 | Secondary Pins |
|-------------|---------------|----------------|---------------|----------------|
| PE-65837 | 1:1.08 | 3-5 | 1:1.36 | 1 - 5 |
| PE-65839 | 1:1 | 3-5 | 1:1.26 | 1 - 5 |
| PE-65866 | 1:1 | 2-3 | 1:1.26 | 1 - 3 |
| PE-68646 | 1:1.58 | 3-5 | 1:2 | 1 - 5 |
| PE-65389 | 1:1 | 3-5 | 1:1.26 | 1 - 5 |
| PE-65566 | 1:1 | 2-3 | 1:1.26 | 1 - 3 |
| PE-65568 | 1:1 | 2-3 | 1:1.26 | 1 - 3 |
| PE-68866 | 1:1 | 2-3 | 1:1.26 | 1 - 3 |
| PE-68826 | 1:1 | 2-3 | 1:1.26 | 1 - 3 |
| PE-68664 | 1:1 | 3-5 | 1:1.26 | 1 - 5 |
| PE-68836 | 1:1 | 2-3/5-6 | 1:1.26 | 1-3/4-6 |

- Standard packaging for surface mount "AN" and "LA" packages is anti-static tubes. Optional Tape & Reel packaging can be ordered by adding "T" suffix to the part number, (i.e. PE-65857T).

- PE-68618 and PE-64950: The fault locate winding is (7-8).

- Safety Agency approvals pending.

- The turns ratio of these devices have been designed, in conjunction with semiconductor vendor recommendations, to allow connections to various terminations (e.g. 75 or 120Ω with the same transformer). For example T1075 can be used with the Siemens PEB 2235 to achieve connection to the 75 or 120Ω cable. For 75 Ω termination, the PEB 2235 requires the following turns ratio: 1:1.57 (Tx) and 1:1.26 (Rx) which can be achieved using pins (1-2):(15-16) for Tx and (10-11):(5-8) for Rx. For 120Ω, the following turns ratio are required: 1:2 (Tx) and 1:1 (Rx), which are pins (1-2):(16-14) for Tx and (9-11):(5-8) for Rx on the T1075.