

Mini-SAS HD

Product Description

Mini-SAS High Density receptacle is the next generation SAS system; the SAS 2.1 standard meets SAS-3 next generation speed and density requirements that provides faster data transmission and more bandwidth for end users. The low-profile system provides 4X and 8X cable-plug options, and the external I/O connectors includes eight sideband signals per 4X port, 1x4 configuration for up to 192 Gbps of total bandwidth. Mini-SAS HD is designed to save space with its increased density and reduced size as compared to the Mini-SAS 2.0 while following complacency with the standard. Mini-SAS HD connector system has a 2-row, right angle connector with data rates reaching 12 Gbps per channel. Mini-SAS HD can up to 24Gps per channel and can meet SAS-4 and PCIe Gen4/5.

Applications			SFF Supported Standards
RAID	Router/Switch	Blade server	Connector Cage Combo SFF-8614
Workstations	Patch panels	Servers	
Rack-mount server	Routers	Storage rack	

Product Specifications - Mini-SAS HD			
CONNECTOR		CAGE	
Materials Specifications			
Housing	Black color, Glass reinforced , Lead Free Solder Reflow, Process Compatible Thermo Plastic	PCB Thickness	3.00 mm (0.118in.) min.
Contacts Base Material	Phosphor Bronze		
Contact Normal Force	50 grams Minimum		
Plating Press-Fit Area	Matte tin or Gold flash options		
Plating Mating Area	Gold		
Operating Temperature	-40°C to +85°C		
Electrical Specifications			
Operating Voltage	30 VDC per contact		
Operating Current	0.5 A per contact		
Differential impedance	100 Ω +/- 10 Ω		
Mechanical Specifications			
Mating Force	62 N max.	Unmating Force	30 N max.
Durability	250 mating cycles		
Options			
Packaging	Tray		
Configurations	1X1, 1X2, 1X4		
Environmental Specifications Options			
RoHS	Yes		
Halogen Free	Yes		
Flammability Rating	UL 94V-0		



Ordering Information

Mini-SAS HD Combo (Cage/Connector)

U92	X	X	X	X	1	X	X	X	X	X		
U92	SERIES DESIGNATION									MOUNTING SCREWS	X	
A	STYLE A - One Row Cage 0° M - Single level 0° (24 Gbps)									0 - No Screws 1 - Mounting Screws (Standard Length of M2 X 0,4, 4,3 Long)		
X	NUMBER OF PORTS IN ROW 1 - 1x1 2 - 1x2 4 - 1x4									CONTACT PLATING 3 - Mating Area Plating 30 μ" (0.76 μm) Gold Over 50 μ" (1.27 μm) to 150 μ" (3.81 μm) of Nickel; Press-Fit Tail Area Plating 15 μ" (0.38 μm) to 60 μ" (1.52 μm) of Matte Tin Over 50 μ" (1.27 μm) to 150 μ" (3.81 μm) of Nickel 7 - Same As "3"; But with Enhanced Chicklet	X	
X	HEAT SINK OPTION 1 - No Heat Sink and No Clip									PACKAGING 1 - Tray T - Tape & Reel A - Tray - Heat Sink & Clip or Light Pipe Ship Assembled	X	
X	EMI SHIELDING 0 - Standard EMI Fingers 1 - Extended EMI Fingers									LIGHT PIPE OPTION 0 - No Light Pipe 2 - 2 Round Light Pipes per port, on Top of the Cage	X	
											OPTIONAL DUST COVER 0 - Without Dust Cover D - With Dust Cover (Ship Loose)	X
											PLATING 1 - Nickel	1



Order Information:

P: 416.291.4401 | F: 416.292.0647 | E: cages@amphenol-highspeed.com

For more information consult factory or visit amphenol-highspeed.com

Product Applications; List represents common uses for the product but is not limited to these uses.

