

# Coaxial Low Pass Filter

## VLFG-1575+

50Ω DC to 1575 MHz



Generic photo used for illustration purposes only  
CASE STYLE: FF704

### The Big Deal

- Excellent power handling, 5.5W
- Temperature stable
- Rugged unibody construction
- Good rejection, 45 dB typical

### Product Overview

VLFG-1575+ is a 50Ω low pass filter built in rugged unibody construction. Covering DC-1575 MHz bandwidth, these units offer good matching within the passband and good rejection in stopband. VLFG-1575+ offer low insertion loss, and excellent power handling capability. It handles up to 5.5W RF input power and provides a wide operating temperature range from -55°C to 125°C.

### Key Features

Feature	Advantages
Low passband insertion loss	Suitable for high performance application.
5.5W Power handling	Supports a range of system power requirements.
Connectorized package	The connectorized package is easy to interface with other devices and well suited for test setups.

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# Low Pass Filter

## VLFG-1575+

50Ω DC to 1575 MHz



Generic photo used for illustration purposes only  
CASE STYLE: FF704

**+RoHS Compliant**

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Features

- Low loss, 1.1 dB typical
- Good rejection 45 dB typical
- Excellent power handling, 5.5W
- Temperature stable
- Connectorized package
- Rugged unibody construction

### Applications

- Military radar applications
- Test and measurement
- Telecommunication and broadband wireless applications


### Electrical Specifications at 25°C

Parameter	F#	Frequency (MHz)	Min.	Typ.	Max.	Unit	
Pass Band	Insertion Loss	DC-F1	DC - 1575	—	1.1	1.8	dB
	Freq. Cut-Off	F2*	1850	—	3.0	—	dB
	Return Loss	DC-F1	DC - 1575	—	15	—	dB
Stop Band	Rejection Loss	F3-F4	2175 - 2400	20	38	—	dB
		F4-F5	2400 - 7000	36	45	—	dB
		F5-F6	7000 - 12000	—	35	—	dB

In Application where DC voltage is present at either input or output port, DC blocks are required.

\* Typically, a ±5% frequency deviation from the stated value may occur on a unit-to-unit basis.

### Functional Schematic



### Maximum Ratings

Operating Temperature	-55°C to 125°C
Storage Temperature	-55°C to 125°C
RF Power Input*	5.5W max. @25°C





\*Passband rating, derate linearly to 1W at 125°C ambient

Permanent damage may occur if any of these limits are exceeded.

### Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)
10	0.06	41.92
100	0.13	29.52
1000	0.59	15.80
1100	0.64	15.95
1400	0.82	20.07
1500	0.94	24.62
1575	1.08	33.09
1850	3.53	11.28
1960	11.49	3.78
2035	21.64	2.19
2100	33.33	1.61
2175	47.80	1.25
2400	61.50	0.76
3000	61.27	0.45
7000	47.10	0.44
8000	39.12	0.43
9000	41.67	0.41
10000	38.68	0.47
11000	33.55	0.65
12000	33.35	0.97

### Typical Frequency Response



### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

