

### Main

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Range of Product              | Hyde Park                                          |
| Sensor Type                   | Ultrasonic sensor                                  |
| Series name                   | Virtu VM1                                          |
| Device short name             | VM1                                                |
| Sensor design                 | Flat form + cylindrical M18                        |
| [Sn] nominal sensing distance | 20.00 in (508 mm)                                  |
| Type of sensing window        | Adjustable                                         |
| Material                      | Plastic                                            |
| Enclosure Material            | Valox                                              |
| Front material                | Glass epoxy                                        |
| Type of output signal         | Analog                                             |
| ISO thread                    | M18 x 1                                            |
| Wiring Technique              | 4-wire                                             |
| [Us] rated supply voltage     | 15...24 V DC overload and short-circuit protection |
| Supply voltage limits         | 13...28 V DC                                       |
| Analogue output range         | 4...20 mA autoslope                                |
| Electrical connection         | 1 male connector M12 4 pins                        |
| Product Specific Application  | -                                                  |

### Complementary

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| [Sd] sensing range              | 2.00...20.00 in (50.8...508 mm)                          |
| Blind zone                      | 2.01 in (51 mm)                                          |
| Transmission frequency          | 300 kHz                                                  |
| Repeat accuracy                 | 1.27 %                                                   |
| Beam angle                      | 5 °                                                      |
| Minimum size of detected object | Cylinder diameter 2.5 mm - up to 200 mm sensing distance |
| Current Consumption             | 40 mA                                                    |
| Maximum switching current       | 40 mA reverse polarity protection                        |
| Height                          | 1.72 in (43.7 mm)                                        |
| Width                           | 0.71 in (18 mm)                                          |
| Depth                           | 1.72 in (43.7 mm)                                        |
| Length                          | 2.58 in (65.61 mm)                                       |
| Net Weight                      | 0.07 lb(US) (0.033 kg)                                   |

### Environment

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Product Certifications                | UL                                       |
| Marking                               | CE                                       |
| NEMA degree of protection             | NEMA 4X indoor use only)                 |
| IP degree of protection               | IP67                                     |
| Ambient air temperature for operation | -22...158 °F (-30...70 °C)               |
| Ambient Air Temperature for Storage   | -40...185 °F (-40...85 °C)               |
| Relative humidity                     | 100 % without condensation               |
| Vibration resistance                  | +/-1 mm 10...55 Hz)IEC 60068-2-6         |
| Shock resistance                      | 30 gn in all 3 axes 11 ms IEC 60068-2-27 |

|                                      |                                         |
|--------------------------------------|-----------------------------------------|
| Resistance to electromagnetic fields | 9.14 V/m (10 V/m) level 3 IEC 61000-4-3 |
| Resistance to fast transients        | 1 kV level 3 IEC 61000-4-4              |

### Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22490 - SENSORS-ULTRASONIC (XX5,6) |
| Discount Schedule     | DS2                                |
| GTIN                  | 03389119064552                     |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 0.14 lb(US) (0.06 kg)              |
| Returnability         | No                                 |
| Country of origin     | US                                 |

### Offer Sustainability

|                           |                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          |  <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                               |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope                                                                                                                                                                                                                                                                                                                                        |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|