



Electrical Characteristics

Nominal Impedance: Non-constant
 Frequency Range: DC to 300 MHz
 Operating Voltage (rms): 500 V maximum at sea level
 Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
 Insulation Resistance: 500 megohms minimum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum

Environmental Characteristics

Temperature Range: -55 °C to +149 °C

	PART	DESCRIPTION
1	Body	Zinc, nickel plated
2	Contact	Brass, gold plated
3	Dielectric	Bakelite

CAD Issue	SN	2	08 Oct 02
First Issue	PDC	1	27 Mar 01
DESCRIPTION OF REVISION	APPVD	ISS	DATE



Cinch Connectivity Solutions
 7-13 Russell Way,
 Widford Industrial Estate,
 Chelmsford, Essex,
 CM1 3AA, UK.
 Tel: +44 (0) 1245 359515
 Fax: +44 (0) 1245 358938

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
 ± 0.2mm unless
 otherwise stated

DRAWN BY:

S Nash

CHECKED BY:

APPROVED BY:

DATE:

08 Oct 02

TITLE:

UHF Flange Mount Jack

PART NUMBER:

VU511

PAGE: 1 of 1