



# Three Phase Rectifier Bridge

$$I_{dAV} = 70 \text{ A}$$

$$V_{RRM} = 1600 \text{ V}$$

$V_{RSM}$	$V_{RRM}$	Type
$V_{DSM}$	$V_{DRM}$	
$V$	$V$	
1700	1600	VVZF 70-16io7



Symbol	Conditions	Maximum Ratings
$I_{dAV}$ ①	$T_C = 85^\circ\text{C}$ , module	70 A
$I_{dAVM}$ ①	module	70 A
$I_{FRMS}$ , $I_{TRMS}$	per leg	36 A
$I_{FSM}$ , $I_{TSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10 \text{ ms}$ (50 Hz)	550 A
	$V_R = 0$ ; $t = 8.3 \text{ ms}$ (60 Hz)	600 A
	$T_{VJ} = T_{VJM}$ ; $t = 10 \text{ ms}$ (50 Hz)	500 A
	$V_R = 0$ ; $t = 8.3 \text{ ms}$ (60 Hz)	550 A
$I^2t$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10 \text{ ms}$ (50 Hz)	1520 A <sup>2</sup> s
	$V_R = 0$ ; $t = 8.3 \text{ ms}$ (60 Hz)	1520 A <sup>2</sup> s
	$T_{VJ} = T_{VJM}$ ; $t = 10 \text{ ms}$ (50 Hz)	1250 A <sup>2</sup> s
	$V_R = 0$ ; $t = 8.3 \text{ ms}$ (60 Hz)	1250 A <sup>2</sup> s
$(di/dt)_{cr}$	$T_{VJ} = 125^\circ\text{C}$ $f = 50 \text{ Hz}$ ; $t_p = 200 \mu\text{s}$	repetitive; $I_T = 50 \text{ A}$ 150 A/ $\mu\text{s}$
	$V_D = \frac{2}{3} V_{DRM}$ $I_G = 0.3 \text{ A}$ $di_G/dt = 0.3 \text{ A}/\mu\text{s}$	non repetitive; $I_T = \frac{1}{2} I_{dAV}$ 500 A/ $\mu\text{s}$
$(dv/dt)_{cr}$	$T_{VJ} = T_{VJM}$ ; $V_D = \frac{2}{3} V_{DRM}$ $R_{GK} = \infty$ , method 1 (linear voltage rise)	1000 V/ $\mu\text{s}$
$V_{RGM}$		10 V
$P_{GM}$	$T_{VJ} = T_{VJM}$ ; $t_p = 30 \mu\text{s}$	10 W
	$I_T = I_{TAVM}$ ; $t_p = 500 \mu\text{s}$	5 W
	$t_p = 10 \mu\text{s}$	1 W
$P_{GAVM}$		0.5 W
$T_{VJ}$		-40...+125 °C
$T_{VJM}$		125 °C
$T_{stg}$		-40...+125 °C
$V_{ISOL}$	50/60 Hz, RMS; $t = 1 \text{ min}$	2500 V~
	$I_{ISOL} \leq 1 \text{ mA}$ ; $t = 1 \text{ s}$	3000 V~
$M_d$	Mounting torque (M5)	5 ±15% Nm
	(10-32 UNF)	44 ±15% lb.in.
Weight	Typ.	100 g

## Features

- Package with copper base plate
- Isolation voltage 3000 V~
- Planar passivated chips
- Low forward voltage drop
- ¼" fast-on power terminals

## Applications

- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

## Advantages

- Easy to mount with two screw
- Space and weight savings
- Improved temperature & power cycling capability
- Small and light weight

Data according to IEC 60747 and refer to a single diode unless otherwise stated.

## Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

IXYS reserves the right to change limits, test conditions and dimensions.

20200117c

Symbol	Conditions	Characteristic Values	
$I_D; I_R$	$V_R = V_{RRM}; V_D = V_{DRM}$	$T_{VJ} = T_{VJM}$	$\leq 5$ mA
$V_T$	$I_T = 80$ A	$T_{VJ} = 25^\circ\text{C}$	$\leq 1.64$ V
$V_{T0}$	For power-loss calculations only		0.85 V
$r_t$			11 m $\Omega$
$V_{GT}$	$V_D = 6$ V	$T_{VJ} = 25^\circ\text{C}$	$\leq 1.5$ V
		$T_{VJ} = -40^\circ\text{C}$	$\leq 1.6$ V
$I_{GT}$	$V_D = 6$ V	$T_{VJ} = 25^\circ\text{C}$	$\leq 100$ mA
		$T_{VJ} = -40^\circ\text{C}$	$\leq 200$ mA
$V_{GD}$	$V_D = \frac{2}{3}V_{DRM}$	$T_{VJ} = T_{VJM}$	$\leq 0.2$ V
$I_{GD}$			$\leq 5$ mA
$I_L$	$t_p = 10$ $\mu\text{s}$	$T_{VJ} = 25^\circ\text{C}$	$\leq 450$ mA
	$I_G = 0.45$ A; $di_G/dt = 0.45$ A/ $\mu\text{s}$		
$I_H$	$V_D = 6$ V; $R_{GK} = \infty$	$T_{VJ} = 25^\circ\text{C}$	$\leq 200$ mA
$t_{gd}$	$V_D = \frac{1}{2}V_{DRM}$	$T_{VJ} = 25^\circ\text{C}$	$\leq 2$ $\mu\text{s}$
	$I_G = 0.45$ A; $di_G/dt = 0.45$ A/ $\mu\text{s}$		
$t_q$	$I_T = 20$ A; $t_p = 200$ $\mu\text{s}$	$T_{VJ} = 25^\circ\text{C}$	$\leq 250$ $\mu\text{s}$
	$V_R = 100$ V; $di/dt = -10$ A/ $\mu\text{s}$		
	$dv/dt = -15$ V/ $\mu\text{s}$ ; $V_D = \frac{2}{3}V_{DRM}$		
$R_{thJC}$	per thyristor / diode; DC		0.9 K/W
	per module		0.15 K/W
$R_{thJH}$	per thyristor / diode; DC		1.1 K/W
	per module		0.157 K/W
$d_s$	Creeping distance on surface		16.1 mm
$d_A$	Creepage distance in air		7.5 mm
$a$	Max. allowable acceleration		50 m/s <sup>2</sup>

