Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSD
Sensor design	Form 80 x 80 x 40
Size	51 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	0.47 in (12 mm)
Discrete output function	1 NO or 1 NC programmable
Electrical connection	Screw-clamp terminals
[Us] rated supply voltage	AC
IP degree of protection	IP67

### Complementary

Detection face	Frontal	
Detector flush mounting acceptance	Non flush mountable	
Material	Plastic	
Front material	Plastic	
Output circuit type	AC	
Cable entry	1 entry tapped for Pg 13.5 cable gland	
Switching capacity in mA	5500 mA	
Switching frequency	<= 10 Hz	
Marking	CE	
Depth	2 in (50.8 mm)	
Height	3.94 in (100 mm)	
Width	3.15 in (80 mm)	
Product weight	1.06 lb(US) (0.48 kg)	

## Environment

Product certifications	CCC
Ambient air temperature for operation	-13158 °F (-2570 °C)

### Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	00785901218265
Nbr. of units in pkg.	1
Package weight(Lbs)	0.140000000000001
Returnability	N
Country of origin	US

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

## Contractual warranty

Warranty period	18 months
-----------------	-----------