XUSZPM5BXPL09

Multi beam muting sensors, Telemecanique Safety light curtains XUSL, Multibeams for arm B coding





Main

Range of Product	Telemecanique Safety light curtains XUSL
Product or Component Type	Multi-beam muting sensors
Device short name	XUSZPM5
Output type	1 discrete solid-state PNP (NO)
[Sn] nominal sensing distance	0.0011.48 ft (03.5 m)
Number of beams	5
Space between beams	0.39 in (10 mm)

Complementary

Complementary		
Product Compatibility	XUSL4M	
Detection system	Through beam	
Response Time	< 100 ms	
Kit composition	Transmitter + receiver Quick start guide	
Emission	IR LED 0.000037008 in (940 nm)	
[Us] rated supply voltage	24 V DC +/- 20 %	
Supply	Via external supply	
Current consumption	42 mA no load	
Output voltage	24 V	
Output circuit type	DC	
Maximum voltage drop	<0.5 V	
Switching capacity in mA	100 mA	
Local signalling	1 green, orange and red LED receiver	
Housing colour	Grey	

Environment

Directives	98/37/EEC - machinery	
	89/336/EEC - electromagnetic compatibility	
Product Certifications	CE	
Safety reliability data	PFHd = 2.73E-7 1/h	
Ambient Air Temperature for Operation	-22131 °F (-3055 °C)	
Ambient Air Temperature for Storage	-22158 °F (-3070 °C)	
Relative Humidity	095 % without condensation	
IP degree of protection	IP65	
Shock resistance	10 gn 16 ms IEC 61496-1	
Vibration resistance	0.35 +/- 0.05 mm 1055 Hz)IEC 61496-1	

Ordering and shipping details

<u> 3 1 - 1 - 3 </u>	
Category	22455-LIGHT CURTAINS - XUSL
Discount Schedule	DS2
GTIN	3389119646482
Returnability	No

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.69 in (17.0 cm)	
Package 1 Width	2.56 in (6.5 cm)	
Package 1 Length	3.94 in (10.0 cm)	
Package 1 Weight	13.76 oz (390.0 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	