



### Main

Range of Product	Telemecanique Photoelectric sensors XU
Accessory / Separate Part Type	Fiber optic
Accessory / separate part category	Sensor accessories

### Complementary

Product Compatibility	XUDA XUYAF
Detection system	Thru beam
[Sn] nominal sensing distance	0.33 ft (0.1 m)
Optic fiber length	6.56 ft (2 m)
External diameter	0.06 in (1.5 mm)
Spot diameter	0.5 mm
Net Weight	0.11 lb(US) (0.05 kg)

### Ordering and shipping details

Category	22481-SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	3389119009287
Nbr. of units in pkg.	1
Package weight(Lbs)	1.20 oz (34.0 g)
Returnability	No
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.69 in (17 cm)
Package 1 width	0.59 in (1.5 cm)
Package 1 Length	6.69 in (17 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

---

Warranty

18 months

---