XVS96BMWN

Electronic alarm, Harmony XVS, white, NPN, mounting support DIN 96, 0...96dB, 16tones, 4 channels, 12...24V AC DC





Main

Range of Product	Harmony XVS	
Product or Component Type	Electronic alarm	
Device short name	XVS	

Complementary

Complementary	
Color	White
Material	PC (polycarbonate) terminal cover
	PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene) body
Marking	CE
Overvoltage category	Class II EN/IEC 61140
Mounting Support	96 mm DIN rail
[Us] rated supply voltage	1224 V DC
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	250 mA 12 V
	292 mA 12 V
	292 mA 24 V
	354 mA 24 V
Clamping Connection Capacity	<= 1 x 1.5 mm²
Width	3.78 in (96 mm)
Height	3.78 in (96 mm)
Depth	2.29 in (58.1 mm)
Net Weight	0.88 lb(US) (0.4 kg)

Environment

Discrete output type	NPN	
Signalling type	16 tones alarm	
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient Air Temperature for Storage	-31158 °F (-3570 °C)	
Ambient Air Temperature for Operation	-4122 °F (-2050 °C)	
IP degree of protection	Panel mounted IP54 EN/IEC 60529	
Noise level	096 dB continuous or intermittent tone)1 m	

Ordering and shipping details

Category	22617-XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	3606480072024
Returnability	No
Country of origin	JP

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.31 in (13.5 cm)	
Package 1 Width	5.55 in (14.1 cm)	
Package 1 Length	5.55 in (14.1 cm)	
Package 1 Weight	18.84 oz (534.0 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	[™] China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	[™] End Of Life Information	

Contractual warranty

Warranty	18 months