


# 11<sup>TH</sup> GEN INTEL® CORE™ PROCESSORS

## conga-TC570



**COM Express®**

- Embedded/Industrial use condition
- Extended temperature options available
- PCI Express Gen 4
- Integrated high performance Xe (Gen 12) graphics with 96 EU
- AI/DL Instruction Sets including VNNI

<b>Form Factor</b>	COM Express® Compact, (95 x 95 mm)   Type 6 connector pinout					
<b>CPU</b>	<b>Processor</b>	<b>Cores/Threads</b>	<b>Base Frequency/max. Turbo</b>	<b>TDP</b>	<b>Graphics</b>	<b>Intel Use Condition</b>
	Core™ i7-1185G7E	4C/8T	1.80 GHz / 4.40 GHz	12-28W	96EU	Embedded Broad Market
	Core™ i5-1145G7E	4C/8T	1.50 GHz / 4.40 GHz	12-28W	80EU	Embedded Broad Market
	Core™ i3-1115G4E	2C/4T	2.20 GHz / 3.90 GHz	12-28W	48EU	Embedded Broad Market
	Celeron 6305E	2C/2T	1.80 GHz / --	15W	48EU	Embedded Broad Market
	Core™ i7-1185GRE	4C/8T	1.80 GHz / 4.40 GHz	12-28W	96EU	Industrial
	Core™ i5-1145GRE	4C/8T	1.50 GHz / 4.10 GHz	12-28W	80EU	Industrial
	Core™ i3-1115GRE	2C/4T	2.20 GHz / 3.90 GHz	12-28W	48EU	Industrial
<b>DRAM</b>	Up to 2 SO-DIMM sockets for DDR4 memory modules up to 32 GByte each (64 GByte total) with 3200 MT/s					
<b>Graphics</b>	Integrated Xe (Gen 12) graphics engine with up to 96 EU (Execution Units)   Supporting 4 independent display units (4x 4k/2x 8K)   Enhanced media (AV1/12b) with up to 2 Vdbox   Next Gen IPU6 with DPHY2.1   DP 1.4					
<b>Display</b>	3x DP/DP++   1x eDP					
<b>Ethernet</b>	1x 2.5 GbE TSN Ethernet via Intel® i225					
<b>I/O Interfaces</b>	8x PCIe Gen3   PEG support x4 (PCIe Gen4) 4x USB 3.1 Gen 2   8x USB 2.0 2x SATA III (6Gb/s)   SPI   2x UART   8x GPIO					
<b>Audio</b>	HDA interface					
<b>congatec Board controller</b>	Multi Stage Watchdog   non-volatile User Data Storage   Manufacturing and Board Information   Board Statistics I <sup>2</sup> C bus (fast mode, 400 kHz, multi-master)   Power Loss Control   Hardware Health Monitoring   POST Code redirection					
<b>Embedded BIOS Feature</b>	AMI Aptio® UEFI firmware   32 Mbyte serial SPI with congatec Embedded BIOS feature   OEM Logo   OEM CMOS Defaults   LCD Control   Display Auto Detection   Backlight Control   Flash Update					
<b>Security</b>	Trusted Platform Module (TPM 2.0)					
<b>Power Management</b>	ACPI 5.0 with battery support					
<b>Operating Systems</b>	Microsoft® Windows 10   Microsoft® Windows 10 IoT Enterprise   Microsoft® Windows IoT 10 Core   Linux   Android   Yocto   RTS Hypervisor					
<b>Temperature Range</b>	Commercial: Operating Temperature: 0 to +60°C		Storage Temperature: -20 to +80°C			
	Industrial: Operating Temperature: -40 to +85°C		Storage Temperature: -40 to +85°C			
<b>Humidity</b>	Operating: 10 to 90% r. H. non cond.					
	Storage: 5 to 95% r. H. non cond.					
<b>Size</b>	95 x 95 mm <sup>2</sup>					

# conga-TC570 | Order Information

